

CONTINUOUS 3/8" BEAD OF SEALANT PER WINDOW MANUFACTURER'S INSTRUCTIONS

MECHANICALLY FASTEN AS NECESSARY

GRACE VYCOR MAF

NAILING FLANGE

EXTERIOR SHEATHING

MECHANICALLY FASTEN AS NECESSARY

GRACE VYCOR MAF

NOTES:

- A. VISIT GRACECONSTRUCTION.COM FOR THE MOST CURRENT DETAILS, INSTALLATION VIDEO AND PRODUCT DATA SHEETS FOR FURTHER INFORMATION
- B. INSTALL GRACE VYCOR® MAF IN ORDER AS SHOWN BY NUMBERS
- C. MECHANICALLY FASTEN SILL & JAMB FLASHING ALONG THE EDGE OF THE ROUGH OPENING WHERE THEY WILL BE COVERED BY THE FLANGE
- D. APPLY APPROPRIATE SEALANT AS PER WINDOW MANUFACTURER'S REQUIREMENTS
- E. MECHANICALLY FASTEN HEAD FLASHING ALONG THE TOP EDGE
- F. CHECK LOCAL BUILDING CODES FOR WEATHER RESISTIVE BARRIER REQUIREMENTS AND INSTALL GRACE VYCOR® MAF WITH WEATHER RESISTIVE BARRIER TO FORM WATER-SHEDDING LAPS
- G. GRACE VYCOR® MAF LIMITED TO WALLS SLOPED GREATER THAN 60°

GRACE
Construction Products
www.graceconstruction.com
toll free 866-333-3726

FLANGED WINDOW
AAMA RECOMMENDATION METHOD-B
GRACE VYCOR® MAF MECHANICALLY ATTACHED FLASHING

Drawing: VCRDET-112

Scale: Not to scale

Effective Date: 05/30/08

Supersedes: NEW